

TRIAX DSG-DCT ATF

DUAL CLUTCH AUTOMATIC TRANSMISSION FLUID

TRIAX DSG-DCT ATF is a full synthetic ultra high performance transmission fluid for dual clutch European DCT / DSG transmissions. This fluid is made with full synthetic and PAO base oils, plus an OEM grade additive system to meet and exceed the requirements for these high performance transmissions. TRIAX DSG features exceptional longevity and is compatible with all dual clutch automotive gear boxes including those manufactured by BMW, Audi / VW, Mercedes Benz, Peugeot, Porsche, Ferrari, Renault, Ford and ZF. Exceptionally high frictional stability and grip characteristics eliminate slippage, prevent gear scuffing and offers complete compatibility with all transmissions seals and gaskets.

TRIAX DSG -DCT ATF is classified as a FILL FOR LIFE product in properly sealed transmissions.

PERFORMANCE HIGHLIGHTS

- Extreme shear resistance and load carrying capacity without shearing
- Exceptional protection for gears, synchros
- Excellent yellow metal protection
- Complete compatibility with all transmission seals and gaskets
- Superior oxidation stability
- Flawless shifting characteristics and zero slippage
- Extremely long fluid life, qualifies for lifetime fill unless otherwise specified by OEM.

SPECIFICATIONS & APPLICATIONS

TRIAX DCT-DSG ATF is recommended for high performance dual clutch 6 speed and 7 speed transmissions from VW, Audi, Mercedes Benz, Ferrari, Porsche and many others. Please see product specification list below.

SPECIFICATIONS:

BMW Drivelogic 7-speed (Getrag)/DCTF-1	Chrysler Powershift 6-speed (Getrag)	Pentosin FFL 2, 3, 4
BMW 6-speed DCT	DCT-1	Peugeot/Citroen DCS 6-speed (GFT)/9734.S2
BMW MTF LT-5	Ferrari 7-speed (Getrag)/TE DCT-3	Renault EDC 6-speed (Getrag)
Borg Warner	Ford/Nissan Powershift 6-speed (GFT)	Shell TF DCT-F3
Bugatti Veyron	Ford WSS-M2C936A	Volvo Powershift 6-speed (GFT)/1161838/1161839
Castrol BOT 341	Ford WSS-M2C200-D2/ XT-11-QDC	VW (Audi, Seat, Skoda) 6-speed
Castrol BOT 450	Mitsubishi TC-SST 6-speed (GFT)	VW/Audi TL 55529 (spec) / G 055 529 A2 or A6 (fluid)
Castrol Transmax Dual	MZ320065 DiaQueen	VW/Audi TL 521 82 (spec) / G 052 182 A2 or A6 (fluid)
Chrysler 68044345 EA & GA	SSTF-1	ZF/Porsche Oil #999.917.080.00

If a specification is listed above, TRIAX LLC guarantees the product meets, exceeds that specification or is safe to use in equipment requiring that application, and is therefore covered by our product warranty.

CHEMICAL PROPERTIES

Viscosity @ 100°C, cSt, ASTM D445	7.03
Viscosity @ 40°C, cSt, ASTM D445	33.6
Viscosity Index, ASTM D2270	181
Pour Point, °C, ASTM D97	-51
Flash Point, °C(F), ASTM D92	221 (430)
Specific Gravity	0.825

Small deviations from these results are expected during the manufacturing process and do not affect product performance or specification compliance.

• All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use, which is strictly to guide consumers as to the application of TRIAX products and convey compatibility or lack thereof.