

TRIAX EURO LV 0W-30

FULL SYNTHETIC EUROPEAN CAR DIESEL AND SELECT GASOLINE ENGINES

TRIAX EURO LV 0W-20 Full Synthetic is a low viscosity, low friction engine oil designed for the latest generation BMW vehicles as well as many other cars requiring a 0W-30 ACEA C2/C3 product. This is a high PAO / Ester content lubricant, with an exceptionally low volatility, superb low temp properties and extreme shear stability. TRIAX Euro LV 0W-20 contains supplemental friction modifiers for improved protection of critical parts, drastically improving the life of turbo-charges, pistons and bearings. It is built with our Nano Boron and Moly friction modifiers for improved friction management, lower friction coefficient for significant engine wear reduction, lower oxidation and higher stability.

PERFORMANCE HIGHLIGHTS

- Excellent shear stability, low volatility and extended drain intervals
- Low temperature pumpability down to -50°C
- State-of-the detergent system to keep your engine clean for 250,000 miles and beyond
- Exceptionally quiet and efficient hydraulic tappets
- Excellent protection for turbo-chargers, preventing premature failure due to oil deposits
- Nearly ZERO deposits on piston rings and valves throughout its life
- Complete protection for Catalytic Converters, Diesel Particulate Filters & SCR (AdBlue) systems
- Maintains film integrity even at very high operating temperatures
- Permits full service for vehicles still in OEM warranty per the specifications listed below.

EXTENDED DRAIN INTERVAL
15,000 miles or 2 Years**
whichever comes first

APPLICATIONS

TRIAX EURO LV 0W-30 is recommended for European high performance engines, specifically designed for BMW, VW / Audi, Mercedes, Volvo and Land Rover engines, turbo or twin-turbo, per the specifications listed below. It is also recommended for any gasoline or diesel powered (with DPF & SCR emission control systems) vehicle requiring a 0W-30 viscosity engine oil, such as Ford, Mazda, Mitsubishi, Nissan and many others requiring a 0W-30 ACEA C2 engine oil.

SPECIFICATIONS

BMW LongLife 12 FE+
VW 504.00 / 507.00
ACEA C2, ACEA C3
MB 229.61 (Suitable for use)
Land Rover
VOLVO 95200377
STJLR.03.5007

CHEMICAL PROPERTIES

VISCOSITY GRADE SAE	0W-30
SPECIFIC GRAVITY @ 60F	0.849
KINEMATIC VISCOSITY @ 40C	53.60
KINEMATIC VISCOSITY @ 100 C	9.9
VISCOSITY INDEX	175
FLASH POINT (C)	226
POUR POINT C (F)	-54 (-65.2)

Small deviations from these results are expected during the manufacturing process and do not affect product performance.

*All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use, which is strictly to guide consumers as to the application of TRIAX products and convey compatibility or lack thereof.

** The drain interval mentioned herein represents the capability of the lubricant and is valid for a mechanically sound engines, with regular oil analysis and without the use of after-market additives.