

TRIAX CVT ATF

FULL SYNTHETIC OEM GRADE CVT TRANSMISSION FLUID

TRIAX CVT SYNTHETIC ATF is a universal, wide spec formulation specifically formulated for today's technologically sophisticated variable transmissions. This product eliminates the need to stock multiple, limited OEM brands. TRIAX SYNTRON CVT SYNTHETIC has equal, and in most cases, better performance than the most common North American CVT Fluids being supplied by leading OEMs. TRIAX CVT SYNTHETIC ATF provides engineered anti-shudder performance for smooth transfer of power, exceptional anti-oxidation and anti-wear protection in highly sophisticated variable transmissions.

SPECIFICATIONS & APPLICATIONS

This product meets or exceeds the performance requirements by most CVT OEMs. It is compatible with virtually all CVT fitted street vehicles, passenger cars, SUVs and trucks made by BMW, Porsche, Nissan, Honda, Toyota, Subaru, Mercedes Benz, Kia and many others.

BMW/Mini 83 22 0 136 376, BMW/Mini 83 22 0 429 154
Chrysler/Dodge/Jeep Mopar NS-2/CVTF+4, 05191184AA
Daihatsu Ammix CVTF-DC, Ammix CVTF-DFE
Ford Mercon® C/23/30, XT-7-QCFT, WSS-M2C933A, M2C928-A
GM DEX-CVT®, 22688912, 152346, 15231847, 15250985
 CVT (GM 19260800, 19299096)
 DEX-CVT (AC Delco 15234609, 15250985, 15231847, 22688912)
Honda/Acura Genuine Honda CVT Fluid Multimatic (HMMF)
Honda/Acura 08260-9904, 08200-9006, 08200-HCF2
Honda/Acura 5030119 08798-9018, Honda HCF-2
Hyundai/Kia SP-CVT 1, Genuine CVTF, IVTF-SP-CVT-1
Mazda CVTF, Mobil CVT 3320
Mercedes Benz 236.20, 722.8, 001 989 46 03, EM-CVT
Mitsubishi Dia Queen CVTF-J1, Dia Queen CVTF-J4, MZ313973, MZ320185

Nissan NS-1, NS-2, NS-3, 999MP-NS200P, KLE52-00004
Nissan WSS-M2C-936-A
Subaru High Torque CVT Fluid SOA748V0200
Subaru Lineartronic® CVTF, Lineartronic CVTF-III
Subaru Lineartronic® CVTF II, K0425Y0711, K0425Y0710
Subaru High Torque CVTF LV
Subaru CV-30, TF690, TR580, TR690, e-CVFT
Subaru i- CVT FG, SOA427V1600, SOA427V1610
Subaru SOA427V1660, SOA868V9245
Suzuki TC, NS-2, CVT Shell Green IV, CVTF Green2
Toyota/Scion TC, FE, 08886-02105
Volvo 5344959-6, ZF VT1-27T, VT1-13A
VW/Audi G052852, G 052 180 A1, G 052 180 J1 G 052 516, TL 52180

PERFORMANCE HIGHLIGHTS

- Extreme shear resistance and viscosity stability
- Exceptional torque transfer (dynamic friction)
- Meets requirements for 98% of all CVT vehicles on the market
- 10-15 degrees lower transmission operational temperature in most cases
- Excellent hot / cold temperature performance
- Helps to control transmission shudder and provide excellent vehicle driveability
- Provides a wide range of seal compatibility, not harmful to synthetic rubber seals
- Excellent lubricating characteristics for quiet operation and smooth shifting in approved transmissions
- Superb protection against rusting and corrosion
- Superb foaming resistance – contains high quality anti-foaming agents
- Excellent viscosity stability (very high viscosity index) to help assure a adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- Facilitates smooth shifting throughout its life · Unmatched oxidation stability

CHEMICAL PROPERTIES

Property	Value
Density at 15°C(kg/m ³)	0.8492
Viscosity at 40°C mm ² /s	33.69
Viscosity at 100°C mm ² /s	7.28
Viscosity Index	192
Pourpoint °C	-51 (-59 F)
Flashpoint °C	220
Brookfield Viscosity (-40C)	9500
Color	OEM GREEN